

CAP MASTIC

ACRYLIC JOINT SEALANT

DESCRIPTION

CAP MASTIC acrylic sealant is a one-component sealing compound based on acrylic resin. Suitable for filling of cracks and joints indoors or outdoors

USES

A general purpose sealant for sealing of

- Low movement construction joints between brick, concrete, timber etc.
- Filing joints and cracks in ceilings.
- Filling joints of wood plaster, ceramic elements and for joint in wooden cases and containers.
- smoothing cracked surfaces

ADVANTAGES

- Very good application and tooling properties, Elastoplastic
- Can be painted over
- UV resistant
- Does not contain solvents
- Easy application
- Adheres to moist and absorbent Substrates
- Can be thinned by water to make primer

PRODUCT DATA :-

Appearance	: A smooth viscous paste
Colour	: White, Grey
Specific Gravity	: 1.5
Solid Content	: 80+2%
Sag	: No sag in 30 mm channel
Skimming time	: 30 minutes
Curing time	: cures by evaporation of Water 1-2 weeks depending upon temp.
Flammability	: Non flammable (water born)
Application	: use between 5°C and 80°C
Weight Loss	: 25% approx.

APPLICATION PROCEDURE

Surface Preparation:

For good adhesion, the joint surface must be sound, clean and dry. Depending on the substrate, if necessary, entirely remove traces of old sealing

materials and other residues. In order to obtain neat edges, we recommend masking the edges of the joint with a suitable type of tape.

In case of deeper joints use polyethylene based baker rod to maintain the depth of sealant.,

APPLICATION:

Fill the joints with CAP MASTIC using caulking tools or caulking gun, special consideration should be given to the adhesion of edges. Use of primer (diluted CAP MASTIC with 1to 2 part of water) is recommended the wide to depth ratio should be equal on moving joints.

PAINTING

Properly cured CAP MASTIC can be over painted using quality grades of latex or oil paints.

CLEAN UP

Hands and smears adjacent to the joint can be cleaned or removed with soap and water before sealant cures

PACKAGING

CAP MASTIC is available in standard packing of 5 kg and 25kg Pails.

COVERAGE

The coverage of CAP MASTIC depends on joint size. Refer coverage chart for different size of joints.

SHELF LIFE:

Minimum 12 months sealed original in containers, under recommended storage conditions.

LIMITATIONS:

- Sealant must be protected from water for 24 hours after application
- Do not use externally when rain is imminent.

Coverage

Linear meter per kg

width Depth	0.5 cm	1 cm	1.5 cm	2 cm	2.5 cm	3 cm
1 cm	12.5	6.3	4.2	3.1	2.5	2.1
1.5 cm	8.3	4.2	2.7	2.1	1.6	1.3
2 cm	6.3	3.1	2.1	1.5	1.2	1.0
2.5 cm	5.0	2.5	1.6	1.2	1.0	0.8
3 cm	4.2	2.1	1.3	1.0	0.8	0.7

Rev: 02 Jan 2016

TECHNICAL SERVICE:

Our Technical Service Department is available at any time to advise you in the correct use of this product or any other Ahlia products.

Note: The information presented herein is based on the best of our knowledge and expertise for which every effort is made to ensure its reliability. Although all the products are subjected to rigid quality tests and are guaranteed against defective materials and manufacture, no specific guarantee can be extended because results depend not only on quality but also on other factors beyond our control.

As all Ahlia Technical Data Sheets are updated on a regular basis, it is the user responsibility to collect most recent issue.