

PRODUCT	FEATURES	USES	COVERAGE / DOSAGE	SPECIFICATION /TEST METHOD	PACKING
<i>Cement Based</i>					
CAPCRETE	Polymer modified cement based trowel able flooring compound for re-surfacing and reinstatement of large areas of concrete.	Provides hard wearing surface to new or old concrete floors in wear houses, factories etc with high abrasion resistance, high impact and non-dusting.	23.0 kg/m ² at 10 mm thickness.	ASTM C-109	25 kg bag.
CAP DRY SHAKE HARDENER	Pre-blended dry shake surface hardener consisting hydraulic binder and high quality inert mineral aggregate.	To provide continuous protection to concrete floors against wear, impact and abrasion.	3.0 kg/m ² for light duty 5.0 kg/m ² for medium duty 7.0 kg/m ² for heavy duty	ASTM C-109 BS 8204 PART-2	25 kg bag.
CAP LEVEL TOP	Pre-blended, free flowing, self leveling cementitious floor leveling compound.	To smooth out surface irregularities prior to laying final floor covering.	Usually 7.0 m ² /bag at 2mm thick.	ASTM C-109	25 kg bag.
CAP EMERY TOP	Emery based hard wearing monolithic surfacing	As a shake on topping for flooring areas where high abrasion and impact resistance surface is required	4-8 kg/m ² depending on the level of protection required	ASTM C-109 BS 8204 PART-2	25 kg bag.
<i>Resin Based</i>					
CAPOXY PRIME	low V.O.C adhesion promoting primer	As primer with epoxy base flooring, coating and repair products or stand alone sealer.	5 -7 m ² /liter	Tested by: ASTM C-882 ASTM C-638 ASTM C-883	1 liter pack 4 litre pack
CAPOXY PRIME-SB	solvented base primer and sealer	as primer with epoxy base flooring, coating and repair products	6-8 m ² /litre	In house quality standards	1 liter pack 4 litre pack
CAPOXY PRIME -SPL	Epoxy base Low viscosity penetrating primer and sealer	For priming of damp or dry concrete Capoxy prime SPL can be applied within two days of pouring new concrete.	6- 8 m ² /liters	Tested by: ASTM C-882 ASTM C-638 ASTM C-883	1 liter pack 4 litre pack

PRODUCT	FEATURES	USES	COVERAGE / DOSAGE	SPECIFICATION /TEST METHOD	PACKING
CAPOXY FLOOR-500	100% solid, solvent free high performance epoxy coating	High performance floor coating for industrial floors , laboratory and walk ways	3.5 to-4 m ² /liter	ASTM D-1308 ASTM D-4541	4 liter kit 20 liter kit
CAPOXY FLOOR -SL	100% solidSelf leveling, hard wearing floor topping	Industrial floors where good abrasion and chemical resistance required	3m ² / 20 liter kit @ 4.8mm thickness	ASTM D-1308 ASTM D-4541	20 liter kit
CAPOXY FLOOR-310	Solvented, high performance epoxy resin floor and wall coating	Suitable to use in production assembly area, workshops and showrooms	4-4.5 m ² /liter	ASTM D-1308 ASTM D-4541	4 liter kit 20 liter kit
CAPOXY MORTAR TA	Heavy duty three component resin base mortar	To be use as monolithic surfacing /topping where high mechanical, chemical and abrasion resistance required	2.8 m ² / 30 kg kit@ 5mm thick	Tested to ASTM C-722	30 kg Kit
<i>Urethane Based</i>					
CAP URETHANE-VARNESH	2 Component polyurethane clear with excellent gloss retention, clarity, smoothed,tough and elastic and resistance for water and abrasion	"priming and sealing coat ,decorative and protective topcoat interior or exterior on concrete ,masonry ,cement rendering,metaland wooden substrates "	liter/14 to 20 m ²	In house quality standards	4 liter kit 20 liter kit
CAP URETHANE-GLOSS	2 Component polyurethane top coat with excellent color retention,heavy duty coating over a wide range of substrates,tough, elastic high mechanical resistance to water,abrasion and solvents	decorative and protective top coat interior or exterior tpo coat over an epoxy mastic system on concrete, masonry,cement rendering,metaland wooden substrates	liter/7.9 to 11.8 m ³	In house quality standards	4 liter kit 20 liter kit
CAP URTHANE-FLAT	2 Component polyurethane top coat with excellent color retention ,tough,elastic,high mechanical resistance,resistance for water, abrasion and solvents	decorative and protective top coat interior or exterior tpo coat over an epoxy mastic system on concrete ,masonry,cement rendering,metaland wooden substrates	liter/7.9 to 11.8 m ³	In house quality standards	4 liter kit 20 liter kit