

JOINTING COMPOUND & FIXING MORTAR

PRODUCT	FEATURES	USES	COVERAGE / DOSAGE	SPECIFICATION /TEST METHOD	PACKING
<i>Cement Based</i>					
CAP TILE FIX T.G	Pre-blended, cement based polymer modified tile adhesive for quick and effective bonding in thin or thick bed fixing.	For bonding of ceramic wall and floor tiles, glass and ceramic mosaics directly on sound rough uneven surfaces.	Varies with bed thickness. For more details refer technical data sheet.	BS 5980 Type I Class AA	25 kg bag.
CAPTILE ADHESIVE	Premixed polymer modified cementitious tile fixing mortar for fixing ceramic, terrazzo and mosaic tiles to cementitious substrate.	For adhering ceramic wall and floor tiles ,glass and ceramic mosaic	Varies with bed thickness. For more details refer technical data sheet.	BS 5980 Type I Class AA	25 kg bag
CAP TILE GROUT	Premixed cementitious compound, modified by the inclusion of various additives possessing excellent adhesion.	Grouting of tile joints up to 12mm wide in both floor and wall applications.	Varies with joint width and depth. For more details refer technical data sheet.	BS-CP 5385 Part I	10 kg bag
CAP TILE WALL GROUT	Cementitious fine powder on mixing with water, gives a smooth easily applied creamy paste for smooth clear grouting of ceramic tiles.	Grouting of ceramic wall tile joints up to 4mm wide.	Varies with joint width and depth. For more details refer technical data sheet.	BS-CP 5385 Part I	10 kg bag
WIGHT BLOCK MORTAR	"is apremixed mortar powder aerated light wieght concrete blocks it is a blend of cement ,graded silica sand , adhesion enhancing polymer, white retention agents"	adhering white blocks	3- 5 kg/m ²	In house quality standards	25 kg bag
<i>Acrylic Based</i>					
RANG CERAMIC TILE ADHESIVE	A superoir quality water-born acrylic ready -mixed compound ,blended with carefully selected pigments and extenders	For adhering ceramic wall and floor tiles ,glass, mosaic and ceramic	1 kg/m ²	BS 5980 /80 CLASS A	US gallon 5 US GALLONS
<i>Epoxy Based</i>					
CAPOXY CTG-10	Three component epoxy system for fixing ceramic tile and to be use as jointing mortar.	For fixing ceramic glass and mosaic wall and floor tiles , For Grouting tile joints	Varies with bed thickness and joint width and depth. For more details refer technical data sheet	ANSI -A-118.3-1992	10 kg kit
<i>Render Stucco And Plaster</i>					
CAP SPATTER FINISH	Mineral base textured facing material for the application of cement and gypsum based plaster	To achieve a rough surface over exterior or interior fair face concrete for subsequent plastering.	6 to 7 m ² at 2.5 to 3mm thickness	In house quality standards	25 kg bag
CAP RENDER	Polymer modified rendering mortar ,provides a cohesive Non sag smooth finish and excellent adhesion	For interior or exterior plastering over masonry ,cement blocks, works lime stone etc	7.5 m ² at 2mm thickness	In house quality standards	25 kg bag