

# STAMPCRETE COLOUR RELEASER

**ANTIQUE-RELEASE AGENT** 

## **DESCRIPTION**

**STAMPCRETE Colour Releaser** is a dry blend of hydrophobic powders, proprietary ingredients and coloring pigments designed for use in the concrete imprinting process to allow the clean release of texturing tools from the wet concrete surface.

**STAMPCRETE** Colour Releaser adds color variations and highlights to the textured surface, providing an attractive two-color antiqued look that very closely resembles natural materials such as cobblestone, brick, tile and slate.

#### **ADVANTAGES**

- •Allows a clean bond break between fresh concrete and stamping mats.
- •Ads color variation-antiquing affect for stamped surfaces.
- Easy removal process allows for controlled removal to achieve desired shading effect.

#### LIMITATIONS

The final color of the concrete is affected by many factors. It may be a function of the basic concrete mix ingredients (fine aggregate, coarse aggregate, water and cement), the weather, finishing techniques, experience of the applicators, and coloring method used.

#### **COLOUR**

Various colours

#### APPLICATION INSTRUCTIONS

After concrete is colored with Stampcrete Colour Hardener and it reaches the proper set for imprinting, hand broadcast the release powder evenly over the surface to be stamped. Care should be taken not to trowel the release powder into the wet concrete; this will cause a permanent discoloration. After release

powder has been applied, follow your regular procedure for stamping concrete.

#### **COVERAGE**

Each 15 Kg Pail covers approximately 50-60 square meter

#### **SHELF LIFE**

One year when protected from moisture.

#### **PACKAGING**

15 kg/pail

### SAFETY PRECAUTIONS

Use facemask or respirator. Do not allow getting into eyes. Keep out of the reach of children. Prolonged breathing will cause throat and lung irritation. Protect all adjacent areas.

#### **CLEAN-UP**

Clean all tools immediately after each use with clean water. Do not allow sealer to dry on tools. Keep rollers and brushes soaked in water if not cleaned immediately.

#### **SERVICES**

For further information on this product together with advice on application, please contact The Technical Advisory Department of Ahlia Chemicals Co.

#### **TECHNICAL SERVICE:**

Our Technical Service Department is available at any time to advise you in the correct use of this product or any other Ahlia products.

**Note**: The information presented herein is based on the best of our knowledge and expertise for which every effort is made to ensure its reliability. Although all the products are subjected to rigid quality tests and are guaranteed against defective materials and manufacture, no specific guarantee can be extended because results depend not only on quality but also on other factors beyond our control.

As all Ahlia Technical Data Sheets are updated on a regular basis, it is the user responsibility to collect most recent issue.

Rev.: 02 Mar 2015 Page 1 of 1 Ref No.: ACC/R&D/1503/CEM/0073